

Product data sheet

Brass cable gland, PG thread

Item number: HS-K-MPG




Illustrations may be similar

Material:	Brass nickel-plated
Sealing/Clamping insert::	Chloroprene, Prebunan, Polyamide 6
Connection thread:	PG7; PG9; PG11; PG13,5; PG16; PG21; PG29; PG36; PG42; PG48
Thread standard:	PG, according to DIN 40430
Clamping range mm:	3.0 - 6.5; 5.0 - 10.0; 30.0 - 38.0; 34.0 - 44.0; 4.0 - 8.0; 10.0 - 14.0; 13.0 - 18.0; 18.0 - 25.0; 22.0 - 32.0; 6.0 - 12.0
Thread length mm:	8.0; 14.0; 6.0; 9.0; 6.5; 7.2; 12.0
Wrench size mm:	SW 20; SW 58; SW 17; SW 30; SW 40; SW 50; SW 64; SW 22; SW 24; SW 14
Temperature range:	-40°C to +100°C
Protection class:	IP66 / IP68
Test standard:	Integrated strain relief according to EN50262
Approvals:	UL
RoHS compliant:	Yes
Packaging unit:	50; 10; 25; 5

For individual advice, please feel free to contact us by email:

Subject to changes and errors.



Product link