


Product data sheet

Heat shrink tubingShrink ratio 2:1 high temperature resistant Kynar series

Item number: HS-KY



Illustrations may be similar



Material:	Cross-linked Kynar
Color:	transparent
Dim. D inches:	3/64; 1/16; 3/32; 1/8; 3/16; 1/4; 3/8; 1/2; 3/4; 1; 1 1/2
Ø before shrinkage / Ø after shrinkage:	9,5 mm / 4,8 mm; 12,7 mm / 6,4 mm; 19,1 mm / 9,5 mm; 25,4 mm / 12,7 mm; 38,1 mm / 19,0 mm; 1,2 mm / 0,6 mm; 1,6 mm / 0,8 mm; 2,4 mm / 1,2 mm; 3,2 mm / 1,6 mm; 4,8 mm / 2,4 mm; 6,4 mm / 3,2 mm
Wall thickness after complete shrinkage (mm):	0,28; 0,20; 0,23; 0,36; 0,41; 0,51
Min. temperature for complete shrinkage:	175°C
Operating temperature:	-55°C bis + 175°C
Approval:	UL
RoHS III compliant:	Yes
Packaging unit in meters:	150 roll; 75 roll; 1.22 m rod

For individual advice, please feel free to contact us by email:

Subject to changes and errors.



Product link